



**BARCODE MACHINE READABLE
ELECTRONIC TICKET DISPENSER
Model TD-3020**



Model TD-3020 Ticket Dispenser

FEATURES:

- Direct Interface to Controller Series II revenue control equipment
- Uses pre-printed barcode tickets
- Reliable thermal print technology
- 24VDC low voltage operation
- Optional Internal Batteries allow for operation during power interruptions
- Machine readable Bar code AutoRead
- Rugged rust-resistant zinc plated steel construction.
- Built-In thermostatically controlled heaters.
- Large back-lit LCD displays Date & Time, and optional programmable message.
- Optional built-in intercom
- On-Line Operation
- Tickets 7 mil thick, 4.75" by 2.85"
- Large capacity rolls up to 5000 tickets.
- Easy side access ticket roll loading.
- Optional three parts valet tickets.

SysParc, Inc.
8841 Wilbur Avenue
Northridge, CA 91324

Phone: 818 - 775 - 1832
Fax: 818 - 775 - 1834
Website: www.sysparc.com



I. Purpose:
The **SysParc** Model TD-3020 Ticket Dispenser is a revenue control device that provides a "vend" signal when a ticket is issued. This "vend" signal causes a lift-arm barrier gate to activate, and allow access into the facility.

- II. Features & Functions:
- A. The **SysParc** Model TD-3020 Barcode Ticket Dispenser is designed to issue a printed date & time, barcode machine readable ticket to an entering parking patron.
 - B. The **SysParc** TD-3020 is activated by a push-button, loop detector, treadle, or other triggering device.
 - C. The Ticket Dispenser issues one ticket to each entering parking patron from a continuous 4,000 ticket roll.
 - D. Each **SysParc** ticket may be fully preprinted with general facility location and contract disclaimer data.

- III. Physical Description:
- A. The Ticket Dispenser's overall dimensions are 15" wide, by 20" deep, by 45" in height. It weighs 95 pounds without ticket roll.
 - B. The electrical power requirements for the Ticket Dispenser are 115VAC at 60Hz, or 220VAC at 50Hz. An internal UL approved step-down transformer converts this current into the 24VDC required to power all of the electrical circuitry within the device.
 - C. Each **SysParc** ticket dispenser is equipped with an internal back-up battery to provide continued service even in the event of a general power outage.
 - D. The Ticket Dispenser contains a micro-processor controlled mechanism which includes a date/time clock calendar. This microprocessor may be programmed with its operating parameters remotely via available RS-232 communications connection.
 - E. The Ticket Dispenser is constructed of heavy duty rolled steel, which is zinc plated for rust inhibition, and then powder coated with sealing rust resistant paint. The standard color is white, but the device may be ordered with special paint colors.

- F. Each ticket is cut from the roll with an automatic self-sharpening cutter.
- G. Each ticket is printed at time of issue with the current date & time, lane location number, and a sequential ticket number. This data is printed in both man-readable. The pre-printed barcode machine-readable will transmitted to the CSII at the time of the ticket issue.

